


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00398	Connector, mono plug, 2.5xL19.6 mm, brass, nickel plated, molding style	1	
2	30-00177	Wire, 2C BC, 28 AWG, 300V, 80C, 3.8 mm, foil + shield, PVC	1	
3	24-00028	Overmold, PVC, black	1	



Wiring Diagram	
50-00398	wire color
tip	red
sleeve	white

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>		
A	5/24/2010	Initial release		RoHS and REACH compliant			
A1	9/6/2011	Updated specifications	Verified:	Function test: no open, no short circuit, no intermittent			
A2	3/28/2012	Updated wire part number	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:			
A3	9/17/2012	Updated connector to 50-00269		Cable, 1830 mm, 2.5 mm 50-00398 slim mono plug to 5 mm tinned, 28 AWG, 30-00177, shielded		Size: A Part number: 10-00343	
A4	10/9/2014	Updated connector			Scale: 1:5		Sheet 1 of 1