

# Industrial, Scientific and Medical (ISM) Antennas

# molex

ISM Standalone Antennas combine high RF performance with ease of integration over 433, 868 and 915 MHz bands for advanced industrial, scientific and medical devices

## Features and Benefits

433 MHz ISM Flexible Antenna (Series 204287)


**Topside of the poly-flexible antenna**  
Makes for easy peel-and-stick mounting anywhere within the device chassis

**Double-sided adhesive on the antenna reverse**  
Enables instant application anywhere on the inner wall of the device chassis by just removing its tape liner

**6 Micro-coaxial Cable Length options (50, 100, 150, 200, 250, 300mm)**  
Extends connectivity for maximum design flexibility

868, 915 MHz Balanced, Dipole ISM Flexible Antenna (Series 206764)

868, 915 MHz ISM Flexible Antenna with MobiliquA\* Technology (Series 105262)



## Applications

### Industrial

- Smart homes (security, alarm)
- Smart meters
- Remote keyless entry systems
- Drones

### Scientific

- Optical connectivity solutions
- Underwater sensor networks


### Medical

- Diathermy therapeutic devices
- Microwave ablation machines

**UFL-type connector**  
Secures to the application's device radio



Drones



Underwater Sensor Networks



Diathermy Therapeutic Device

\*The MobiliquA antenna technology incorporates proprietary bandwidth enhancing technologies, which have been used successfully in Molex standard and custom antenna designs. The technology is designed to improve impedance bandwidth in any application with a wireless interface antenna, including mobile phones, smart phones, portable TVs, and standard antennas in industrial applications. Traditional passive antenna structures are based on meandered antenna patterns, with limitations on manufacturing tolerances and mechanical properties. MobiliquA technology enables simple mechanical and robust antenna designs that minimize efforts needed for iterative retuning during each build cycle.

## Specifications

### REFERENCE INFORMATION

Packaging: Tray (105262),  
PET Film (204287, 206764)  
Reference Platform: PC/ABS material block of 2mm  
thickness (204287, 206764); PC material block  
of 2.5mm thickness (105262)  
Designed In: mm  
RoHS: Yes  
Halogen Free: Yes

### ELECTRICAL

RF Power (Watt): 2  
Return Loss (dB): Refer to Product Specifications  
Average Total Radiation Efficiency(%):  
Refer to Product Specifications  
Peak Gain (dBi): Refer to Product Specifications  
Input Impedance (ohms): 50

### MECHANICAL

Refer to Product Specifications

### PHYSICAL

Housing: FPC  
Flammability: UL 94V-0  
Plating: Refer to Sales Drawings  
Operating Temperature:  
-30 to 85°C (204287, 206764)  
-40 to 85°C (105262)

## Ordering Information

Series No.	Frequency Bands (MHz)	Dimensions (mm)
<u><a href="#">206764</a></u>	868, 915	87.40 by 12.40mm
<u><a href="#">105262</a></u>	868, 915	79.00 by 10.00mm
<u><a href="#">204287</a></u>	433	90.00 by 40.00mm

[www.molex.com/link/standard\\_antennas.html](http://www.molex.com/link/standard_antennas.html)