

SMD Power Inductor

0624CDMCC/DS



Description

- Metal compound molding type construction.
- Magnetically shielded.
- Low audible core noise.
- Suitable for large current.
- LxWxH: 7.3x6.8x2.4mm Max.
- Product weight:0.6g (Ref.)
- Moisture Sensitivity Level: 1



Environmental Data

- Operating temperature range: -55°C~+125°C(including coil's self temperature rise)
- Storage temperature range: -55°C~+125°C


Packaging

- Carrier tape and reel packaging.
- 1500pcs/Reel.

Applications

- Qualified consumer-level applications (Ideally used in tablet PC, LCD display , Server application). High current, POL converters.
- Low profile, high current power supplies.
- Battery powered devices.
- DC/DC converters in distributed power systems.

Dimension - [mm]




Note: This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.

SMD Power Inductor


0624CDMCC/DS



Recommended Land pattern - [mm]



Wire Connection



SMD Power Inductor

0624CDMCC/DS



Electrical Characteristics



Part Number	Inductance [Within] (μ H) ※1	D.C.R. at 20°C max(typ) (m Ω)	Saturation Current at 20°C(A) ※2	Temperature Rise Current (A) ※3
0624CDMCCDS-R08MC	0.08 \pm 20%	0.85 (0.70)	85.00	42.00
0624CDMCCDS-R10MC	0.10 \pm 20%	0.96 (0.80)	47.00	40.00
0624CDMCCDS-R12MC	0.12 \pm 20%	0.96 (0.80)	39.00	40.00
0624CDMCCDS-R15MC	0.15 \pm 20%	1.08 (0.90)	37.00	38.00
0624CDMCCDS-R22MC	0.22 \pm 20%	3.00 (2.50)	36.10	22.00
0624CDMCCDS-R33MC	0.33 \pm 20%	4.10 (3.50)	28.50	20.50
0624CDMCCDS-R47MC	0.47 \pm 20%	5.10 (4.50)	24.50	17.50
0624CDMCCDS-R56MC	0.56 \pm 20%	6.50 (5.50)	20.00	15.40
0624CDMCCDS-R68MC	0.68 \pm 20%	7.00 (6.20)	18.80	15.00
0624CDMCCDS-1R0MC	1.00 \pm 20%	9.60 (8.00)	16.20	12.60
0624CDMCCDS-1R5MC	1.50 \pm 20%	19.20 (16.00)	15.00	8.70
0624CDMCCDS-2R2MC	2.20 \pm 20%	28.00 (23.00)	12.80	7.00
0624CDMCCDS-3R3MC	3.30 \pm 20%	48.00 (40.00)	10.60	5.50
0624CDMCCDS-4R7MC	4.70 \pm 20%	54.00 (45.00)	7.60	4.80
0624CDMCCDS-6R8MC	6.80 \pm 20%	66.00 (55.00)	6.70	4.20
0624CDMCCDS-100MC	10.00 \pm 20%	101 (92.00)	5.50	3.10
0624CDMCCDS-150MC	15.00 \pm 20%	160 (145)	3.70	2.50
0624CDMCCDS-220MC	22.00 \pm 20%	242 (222)	3.20	1.90

※1 Measuring frequency Inductance at 100kHz , 1.0V

※2 Saturation current: The actual value of DC current when the inductance is over 70% of its initial value. (at 25°C)

※3 Temperature rise current: The actual value of DC current when temperature of coil rise is $\Delta T=40^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$) Board conditions: FR4, Copper=70 μ m, four-layer PWB, t=1.6mm.

Solder Reflow Condition



Note: This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.

SMD Power Inductor


0624CDMCC/DS




Saturation Current & Temperature Rise Graph

— L (20°C) — ΔT


1. 0624CDMCCDS-R08MC




2. 0624CDMCCDS-R10MC




3. 0624CDMCCDS-R12MC




4. 0624CDMCCDS-R15MC




5. 0624CDMCCDS-R22MC




6. 0624CDMCCDS-R33MC




7. 0624CDMCCDS-R47MC



8. 0624CDMCCDS-R56MC



9. 0624CDMCCDS-R68MC




SMD Power Inductor


0624CDMCC/DS




10. 0624CDMCCDS-1R0MC




11. 0624CDMCCDS-1R5MC




12. 0624CDMCCDS-2R2MC




13. 0624CDMCCDS-3R3MC




14. 0624CDMCCDS-4R7MC




15. 0624CDMCCDS-6R8MC




16. 0624CDMCCDS-100MC



17. 0624CDMCCDS-150MC



18. 0624CDMCCDS-220MC



For sales office information, please [click here](#) to visit our website.