

Specification Sheet

Part Number: T150R0UVX2



Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg

Article Number	111-15206
Type	T150R(U)
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .• Head design provides high tensile strength with very low insertion force.
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg

Global Part Name

T150R(U)-PA66UV-BK

Minimum Tensile Strength (Imperial)

175.0

Minimum Tensile Strength (Metric)

780.0

Length L (Imperial)

15.4

Length L (Metric)

390.0

Identification Plate Position

none

Releasable Closure

No

Variant

Inside Serrated

Width W (Imperial)

0.35

Width W (Metric)

8.9

Bundle Diameter Min (Imperial)

0.32

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

4.1

Bundle Diameter Max (Metric)

104.1

Thickness T (Imperial)

0.075

Thickness T (Metric)

1.9

Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909987