	D I	ш		ш		D	0		σ	A		_
4	R 22.6 Max () () () () () () () () () () () () ()	Deart V	S				<image/>	YOUT SHOWN AS EXAM	WPLE			4
C N	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8 -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		ing Shown as ex	Connector dimensionDimNominalA58.7±0.3B42.85+0.1/-0.1R32.5MaxS55.6±0.4W3+0.9/-0.1V THREADM37x1-6g	5		due to a use the Specifications (professio	not be liable for any no of the Products which issued by either of the onal recommendation Country FR PN: 8D725F3	does not comply e Parties or by a tl , technical notice. Jurisdiction Not	with hird party		2
	-Temperature Range <u>:</u> -65°C to +200°C -Salt Spray : 48 hours					A 03-10-20	D16 First Release	n hu			MOD N°	
	-Mass : 64.63 g ± 10%					Designed By:	Date:		CU	STOMER DRAWING	MODIN	
					TITLE		Aluminium R	eceptacle 8	D series			
	BASIC SERIES:8D7SHELL TYPE : Jam nut ReceptacleCONTACT TYPE : Standard Crimp Contact	- 25 F 35 A			ENTATION : A	SCALE NA SOURIA	U www.	General linear Tolerances: ±		NPRDS / PROJECT 859 This document is the pro SOURIAU it must not be reproduc		1
	SHELL SIZE : 25 PLATING : F = Nickel			CONTACT TYPE : PIN(CONTACT LA	500 Matings) YOUT : 25-35	format A3		SOURIAU D 8D725F35	RG N°	communicated without pe		
	H G	F		E		D	C		В	Α		

Г	± ۵		וד	m	D	0	œ	A		, I	
4	Contact Layout	₽ ⊕ ⊕ ₽ ₽		JAM NUT RECEPTACLE (TYPE 7)							
	2 520 (13.21) +.190 (4.83) 66 4 3 546 (13.87) +.095 (2.41) 67 4 4 555 (14.10) +.000 (0.00) 68 4 5 546 (13.87) 095 (2.41) 69 4	Location X-axis (mm) Y-axis (mm) 000 (0.00) 047 (1.19) 000 (0.00) 142 (3.61) 000 (0.00) 237 (6.02) 000 (0.00) 332 (8.43) 000 (0.00) 427 (10.85)				ØC					
ω	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{r} 0.00 \ (0.00) & -555 \ (14.10) \\ 0.083 \ (2.11) & +.475 \ (12.07) \\ 0.083 \ (2.11) & +.380 \ (9.65) \\ 0.083 \ (2.11) & +.285 \ (7.24) \\ 0.083 \ (2.11) & +.095 \ (2.41) \\ 0.083 \ (2.11) & +.095 \ (2.41) \\ 0.083 \ (2.11) & +.095 \ (2.41) \\ 0.083 \ (2.11) &095 \ (2.41) \\ 0.083 \ (2.11) &095 \ (2.41) \\ 0.083 \ (2.11) &095 \ (2.41) \\ 0.083 \ (2.11) &285 \ (7.24) \\ 0.083 \ (2.11) &285 \ (7.24) \\ 0.083 \ (2.11) &380 \ (9.65) \\ 0.083 \ (2.11) &380 \ (9.65) \\ 0.083 \ (2.11) &475 \ (12.07) \\ 1.06 \ (4.22) & +.427 \ (10.85) \\ 1.06 \ (4.22) & +.323 \ (8.43) \\ 1.06 \ (4.22) & +.237 \ (6.02) \\ 1.06 \ (4.22) & +.142 \ (3.61) \\ \end{array}$				B 43.43	ominal +0/-0.25 +0.25/-0			3	
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{rrrr} 166 (4.22) & +.047 (1.19) \\ 166 (4.22) &047 (1.19) \\ 166 (4.22) &142 (3.61) \\ 166 (4.22) &323 (6.02) \\ 166 (4.22) &237 (6.02) \\ 166 (4.22) &237 (6.02) \\ 166 (4.22) &227 (10.85) \\ 166 (4.22) &522 (13.26) \\ 249 (6.32) & +.496 (12.60) \\ 249 (6.32) & +.380 (9.65) \\ 249 (6.32) & +.285 (7.24) \\ 249 (6.32) & +.095 (2.41) \\ 249 (6.32) & +.095 (2.41) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &190 (4.83) \\ 249 (6.32) &285 (7.24) \\ \end{array}$				due to a use of t the Specifications iss	be liable for any non-conformity on he Products which does not comp ued by either of the Parties or by a l recommendation, technical noti	ly with a third party			
N	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{rrrr} -380 (9.65) \\ -380 (9.65) \\ -475 (12.07) \\ 332 (8.43) & +.444 (11.28) \\ 332 (8.43) & +.332 (8.43) \\ 332 (8.43) & +.332 (8.43) \\ 332 (8.43) & +.237 (6.02) \\ 332 (8.43) & +.142 (3.61) \\ 332 (8.43) &047 (1.19) \\ 332 (8.43) &047 (1.19) \\ 332 (8.43) &142 (3.61) \\ 332 (8.43) &332 (8.43) \\ 332 (8.43) &332 (8.43) \\ 332 (8.43) &332 (8.43) \\ 332 (8.43) &427 (10.85) \\ \end{array}$					Country Jurisdict	on & Control List Iot Listed		2	
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$			A 03 ISS Designed B			CUSTOMER DRAWING	MOD N°		
_	64 +.000 (0.00) +.047 (1.19) 128 + (Applicable to MIL-DTL-38999 only) Shell Arrangement no. Number of contacts Size contacts Service rating 25 -35 128 220 M	479 (12.17) - 279 (7.09) Contact Supersedes location MS27533-35			SCALE		Aluminium Receptacle General linear Tolerances: ±	8D series NPRDS / PROJECT 859 This document is the prope SOURIAU	rty of	1	
	HG		F	E	FORMAT A3	S	OURIAU.COM OURIAU DRG N° 8D725F35AA-C B	it must not be reproduced communicated without perm			